

# **GWT-7.0-1024600-AWMN-01**

## **Ver:10**

**TFT (Thin-Film-Transistor) Color Liquid Crystal Display Module**

<b>GW-</b>	<b>Global Wisdom Display</b>
<b>T</b>	<b>TFT Module</b>
<b>7.0</b>	<b>6.8" Diagonal</b>
<b>1024600</b>	<b>1024 RGB x 600 pixels</b>
<b>A-</b>	<b>Categories of models</b>
<b>W</b>	<b>Amorphous silicon TFT's IPS/ Glare</b>
<b>M-</b>	<b>Transmissive/Normal Black</b>
<b>N-</b>	<b>Without TP</b>
<b>01</b>	<b>Detail Number</b>
	<b>RoHS Compliant</b>

**Global Wisdom Display Co., Ltd**

[www.globalwisdomdisplay.com](http://www.globalwisdomdisplay.com) [www.gwdeshop.com](http://www.gwdeshop.com)

Business services: [GWDsales@globalwisdomdisplay.com](mailto:GWDsales@globalwisdomdisplay.com)

Technical service: [GWDtech@globalwisdomdisplay.com](mailto:GWDtech@globalwisdomdisplay.com)

*Never stop production, stock for sale, support small quantity, full of wide products range*

## Revision History

Revision	Date	Originator	Detail	Remarks
10	2016.07.09	Mary.liu	Initial Release	

## 1. Module General Parameter

Features	Details	Unit
Screen Size (Diagonal)	7.0"	
Panel type	IPS	
Display Mode	Transmissive /Normally Black	
Resolution	1024RGB x 600	
View Direction (human Eye)	FULL VIEW O'clock	Best Image
Module Outline	164.9 (H) x 100 (V) x3.35(T)	mm
Active Area	154.214(H) x 85.92(V)	mm
Dot Size	0.135 (H) x 0.135 (V)	mm
Pixel Arrangement	-Strip	
Polarizer Surface Treatment	Anti-Glare	
Interface	LVDS interface	
Driver IC	EK79001&EK73215	-
With or Without Touch Panel	Without	
Operating Temperature	-20~60	°C
Storage Temperature	-30~70	°C
Weight	TBD	g
Recommend connector	-	

2. Outline Drawing

