



1	YU
2	XL
3	YD
4	XR

- Notes:
1. Type: Film to Glass (雾面防生单膜)
  2. Operating Voltage:  $\leq 5V$
  3. operation Temperature:  $-20^{\circ}C \sim 70^{\circ}C$   
Storage Temperature:  $-30^{\circ}C \sim 80^{\circ}C$
  4. Connect Material: FPC
  5. Life Time Dotted test:  $\geq 1,000,000$  times  
Lineation test:  $\geq 50,000$  times
  6. Response Time:  $\leq 10ms$
  7. Linearity:  $\leq 3\%$
  8. Transmittance:  $\geq 78\%$
  9. Surface Hardness:  $\geq 3H$  (Pencil)
  10. operation force:  $\leq 100g$
  11. Resistance:

(Anti-glare Hard & Mate anti-newton ring coating ITO Film):  $400 \Omega \sim 1100 \Omega$   
(Stand ard ITO Glass):  $100 \Omega \sim 500 \Omega$   
12. Unspecified Tolerance:  $\pm 0.20$   
13. All materials in the drawing coincide with the RoHS & halogen free requirement



Part	NAME:	GW-RTP-10.1-1024600-01
VER: A	U:	mm
APPROVED	S:	1:1
CHECKED	Date:	2018-4-02
DRAWN		