


PIN OUT			
1	XL		
2	YD		
3	XR		
4	YU		



- Notes:
1. Type: Film to Glass (雾面防牛单膜) 5.0INCH
 2. Operating Voltage: $\leq 5V$
 3. operation Temperature: $-20^{\circ}C \sim 70^{\circ}C$
Storage Temperature: $-30^{\circ}C \sim 80^{\circ}C$
 4. Life Time: Dotting test $\geq 1,000,000$ times
Lineation test $\geq 50,000$ times
 5. Connect Material: FPC By Golden plated
 6. Response Time: $\leq 10ms$
 7. Linearity: $\leq 1.5\%$
 8. Transmittance: $\geq 78\%$
 9. Surface Hardness $\geq 3H$ (Pencil)
 10. operation force: $30 \sim 100g$
 11. Resistance:
(Clear hard ITO Film) $x: 400 \Omega \sim 900 \Omega$
(Stand ard ITO Glass) $y: 150 \Omega \sim 450 \Omega$
 12. Unspecified Tolerance: ± 0.20
 13. ROHS must be complied

Global Wisdom Display

Part	NAME:	GW-RTP-5.0-800480-01
VER: A	U: mm	S: 1:1 Date: 2018-4-02
APPROVED	CHECKED	DRAWN

ROHS must be complied Unspecified tolerance is $\pm 0.2mm$